

ZTM Series VZ-20 Portable Radio - VHF/UHF

The VZ-20 is a compact radio communication tool that is equipped with the essential features and quality standards to ensure that users can communicate with ease in mind.

Compact Form Factor

The form factor of this radio is designed to focus on vertical markets such as security, hospitality and retail. The compact size of this radio allows user to seamlessly integrate the radio into the existing business operations.

Simple and Reliable

Characteristic of Vertex Standard portable portfolio, the radio is engineered for ease of use with high quality assurance.

Versatile Scanning

With both scan and priority scan, user can be assured of flexibility of scan modes for better productivity.

Channel Announcement

Upon channel switching, the radio announces the current channel. Users can toggle between channels without having to look at the radio, thus improving work productivity.

Loud and Clear Audio

The 1-Watt speaker ensures important communications are conveyed in any noisy environment.

16 Channels

Up to 16 channels can be stored through programming software. This provides conveniences to the users, avoiding the need to frequently program the radio.

Li-Ion Battery Solutions

1800mAh Li-Ion energy solutions provide up to 13 hours of talk time with 5-5-90 duty cycle comprising 5% transmit, 5% receive and 90% standby.

2-Prong Pin Connector Accessories

The 2-prong pin side connector enables standard audio accessories to be used with this radio, thus lowering the overall cost of ownership.



VZ-20











Specification Sheet - APAC www.vertexstandard.com/a

Additional Features

- Battery Status Indicator
- Battery Saver Mode
- Talkaround
- CTCSS/DCS Encode/Decode
- Channel Announcement
- Internal VOX (Voice Activated Transmit)
- 2-pin accessory connector
- Busy Channel Lockout (BCLO)
- Reverse Burst
- PTT ID

Accessories

- VZ Series Antenna 403-480MHz
- VZ Series Antenna 136-174MHz
- VZ Series Antenna 350-390MHz
- FNB-Z182LI Li-lon 1800 mAh with Fixed Belt Clip
- VZ Series Belt Clip
- CV17 Desktop Charger

	VHF	UHF		
General Specification				
Frequency Range	136-174 MHz	403-480 MHz 350-390 MHz		
Number of Channels	16 channels			
Power Supply Voltage	7.4V nominal			
Channel Spacing	25/12.5 kHz			
Battery Life (5-5-90 duty w/battery saver) 1800mAh Li lon Battery	13 hours			
IP Rating	IP54			
Operating Temperature Range	-13 F to +140 F (-25 C to +60 C)			
Dimension (H x W x D)	4.3 x 2.3 x 1.4 in (109 x 60 x 37 mm) with 1800 mAh Battery			
Weight (Approx.)	270g w/FNB-Z182Li			
Receiver Specification				
Sensitivity	Analog 12 dB SINAD: 0.20uV			
Adjacent Channel Selectivity	65 / 60 dB			
Intermodulation	60 / 55 dB			
Spurious and Image Rejection	70 dB			
Audio Output	1W @ I6 Ohms (INT)			
Hum and Noise	40 dB			
Conducted Spurious Emission	-57 dBm for < I GHz -47 dBm for > I GHz			
Transmitter Specification				
Output Power	5/1 Watt	4/1 Watt		
Modulation Limiting	±2.5kHz			
Conducted Spurious Emissions	-36dBm for <1GHz -30dBm for >1GHz			
FM Hum and Noise	45 / 40 dB			
Audio Distortion	<3%			
Frequency Stability	±1.5ppm			

Authorized Reseller							